

remote display V25N



area of application

Very compactly and lightweight remote-display. Easy readable up to 12 meters.
Applicable for indoor and outdoor including direct sunlight.
Accepts serial strings from PC, PLC or indicator (Systec, Mettler, Schenck, Rhewa, Rinstrum, Sartorius, DS, Every GSE, Soehnle, Pfister, Vishay, Dini Argeo etc.)

technical specification

power supply:	9 - 36 VDC
enclosure:	aluminium, wall thickness 3 mm
protection class:	V25N/G: IP65, V25N/E: IP54
dimension:	V25N/G: 150 x 130 x 60 mm (WxHxD), V25N/E: 174 x 62 x 35
weight:	V25N/G: 0.9 kg, V25N/E: 0.2 kg
character:	6 characters, hight 25 mm (1")
viewing range:	up to 12 meters (40 ft)
reading angle:	140° all around
brightness:	16 position or automatically adjust (sensor)
operating environment:	-20°C bis +60°C (-4°F to 140°F)
input data interface:	RS232, RS485 optional: wireless RF, ethernet
data protocol:	<STX>Data<ETX> <STX>AddressData<ETX> Data<CR><LF> Data<CR> <STX>Data<EOT> <STX>Data<CR> incl. special funktions

options

wireless RF, ethernet
units: kg / t / g / lb / and other

www.vtec.ch/VxxxDGA.htm

manuals, drawings, pc-software, firmware, pictures